



Nelson & Nelson Mfg.
5210 Stadium Blvd, Suite C
Jonesboro AR 72404
870-268-6393 : Cell 219-1019

Installation Instructions 1-18-22

Model SRT-2020+RM

2020+ Spyder RT Rear Mounting Plate

**Steps needed to install your RT Rear Mount Plate.
OEM RT LINQ Rack Required**



1.- First you must have purchased the **OEM RT LINQ RACK**. This rack allows the Mounting Plate to be installed so many other mounting options can be obtained.

Take the new Mounting Plate and lay the plate as shown below. On the RT LINQ RACK. This new mounting plate is designed to mate up with the Rack as shown below. Once placed drill 6 (1/4") holes in the locations shown below in **Red**.



2.- Once the 6 holes are drilled take the supplied bolts, place a bolt in each hole with a spacer separating the plate from the rack. Then take a washer and locknut on each bolt and tighten down not to overtighten. Your Mounting plate is now installed.

This mount is designed to work with the **Optional Cargo Rack** shown below as well as **SHAD Trunk Systems**



We thank you for purchasing our 2020+ RT Accessory Kits. Today we know the needs for accessories that provide a higher level of comfort & style while riding and we have solved that demand with a stylish system that compliments the design of your Spyder®!

spyderextras.com